



Wall-mounted scale approvable

7625, 7627

- ▶ Approvable, class III
- ▶ Only 100 mm overall depth when folded up
- ▶ Scale weight only 22 kg; conveniently installed by one person
- ▶ Wall-mounted scale, protection class IP 68/69K, suited for high-pressure cleaning
- ▶ Terminal: protected against dust and water spray, protection class IP 67
- ▶ Functions: Weighing and taring, zero reset, totaling, order picking, checking, plus / minus weighing










Features

- ▶ Approvable, class III
- ▶ Only 100 mm overall depth when folded up
- ▶ Rear wall height: 200 mm
- ▶ Scale weight only 22 kg; conveniently installed by one person
- ▶ Easy installation with drill template and limited adjustments
- ▶ Overload adjustment is completely eliminated
- ▶ Functions: Weighing and taring, zero reset, totaling, order picking, checking, plus / minus weighing
- ▶ Open design made completely from stainless steel, including load cell
- ▶ Wall-mounted scale, protection class IP 68/69K, suited for high-pressure cleaning
- ▶ Terminal: protected against dust and water spray, protection class IP 67
- ▶ Incl. wall/stand bracket 2503.40.001
- ▶ Version 1, Order No.: .001: No interface, Version 2, Order No.: .002: With RS 232 interface, data transfer to printer or IT
- ▶ Terminal 3010: Simple operation, control lights
- ▶ Terminal 3025: Alphanumeric keyboard, manual tare, barcode management, organization data memories







Products

Order number Variation	Approvable	Division g	Maximum load kg	Model	Platform size mm
7625.40.001 Wall-mounted scale	Yes	20	60	Stainless steel, Terminal 3010	500 x 400
7625.41.001 Wall-mounted scale	Yes	50	150	Stainless steel, Terminal 3010	500 x 400
7625.40.002 Wall-mounted scale	Yes	20	60	Stainless steel, Terminal 3010 with RS 232	500 x 400
7625.41.002 Wall-mounted scale	Yes	50	150	Stainless steel, Terminal 3010 with RS 232	500 x 400
7627.40.002 Wall-mounted scale	Yes	20	60	Stainless steel, Terminal 3025 with RS 232	500 x 400
7627.41.002 Wall-mounted scale	Yes	50	150	Stainless steel, Terminal 3025 with RS 232	500 x 400

Accessories

Order number Variation		Description
2507.01.002		Protective cover 3010/3025
2504.08.001		Bench stand made of stainless steel
2503.40.001		Wall bracket/stand bracket stainless steel
2570.02.004		Custom configuration ATEX zone 2/22, incl. documentation, name plate and 30 m power supply cable without plug
2792.40.001		Alibi memory Micro-SD 4GB, as installation kit (also for fixed value memory and software update)
2792.40.002		Alibi memory Micro-SD 4GB, installed (also for fixed value memory and software update)
2563.21.001		RS 232 interface as installation kit
2563.21.002		RS 232 interface installed
2563.21.005		3rd RS 232 interface as installation kit
2563.21.006		3rd RS 232 interface installed
2550.03.002		Data cable, 9 pin connection 30xx – PC, cable length 2 m
2550.00.008		Data cable, 9 pin connection 30xx – PC, cable length 2–10 m
2795.12.002		Label printer with cutter, printing width up to 104 mm (thermo direct), RS 232
2795.12.004		Label printer with cutter, printing width up to 104 mm (thermo direct), USB
2795.20.001		Label printer, print width up to 108 mm (thermo-direct)
2795.14.005		Tape printer, paper width up to 76 mm (9 pin), RS 232

Accessories







Order number Variation		Description
2795.14.006		Tape printer, paper width up to 76 mm (9 pin), USB
2553.20.003		Portable scanner, wire connection, incl. bench stand bracket and power supply
2553.23.002		Wireless portable scanner Bluetooth, incl. rechargeable battery, base station, RS 232 cable and power supply
2550.03.007		Printer cable 25 pin for printer 2795.14 and 12.001, cable length 2 m
2550.00.009		Printer cable 25 pin for printer 2795.14 and 12.001, cable length 2–10 m
2550.03.010		Data cable for scanner / Precisa / printer 2795.20, cable length 2m
2563.47.001		USB interface as installation kit
2563.47.002		USB interface installed
2550.03.011		USB data cable, connector 30xx – PC, cable length 2 m
2563.45.004		Ethernet interface as installation kit, incl. 10 m patch cable
2563.45.005		Ethernet interface installed incl. 10m patch cable*
2563.49.001		RS422/RS485 interface module as installation kit
2563.49.002		RS422/RS485 interface module installed
2563.12.001		Bluetooth™ module
2554.40.004		Measuring point as installation kit
2554.40.005		Measuring point installed

Accessories

Order number Variation	Description
2550.05.001	Plug-in connection with ID chip installed, approvable section point between scales and display, e.g. for in-ground installation
2550.05.002	Plug-in connection with ID chip installed, approvable section point between scale and display, e.g. for in-ground installation
2550.05.004	Plug-in connection with ID chip, straight plug D=20 mm installed, approvable section point between scale and display
2563.20.004	I/O module relay, as installation kit with socket and cable fitting
2563.20.006	I/O module relay installed with cable fitting
2563.20.007	I/O module PNP, as installation kit with socket
2563.20.009	I/O module PNP, installed with cable fitting
2552.40.001	Relay box (I/O module required) 2 outputs / 4 inputs
2552.41.002	Relay box (I/O module required) with power supply, 6 outputs / 4 inputs
2563.42.007	Profibus DP, as installation kit
2563.42.008	Profibus DP, installed
2563.48.002	Ethernet IP (CIP) interface 3010
2563.44.003	Analog interface as installation kit
2563.44.004	Analog interface installed
2561.40.003	DC/DC converter 12 V - 60 V as installation kit with 5 m cable
2561.40.004	DC/DC converter 12 V - 60 V installed with 5 m cable



Accessories

Order number Variation		Description
2570.01.001		UK power supply installed
2570.01.002		US power supply installed
2570.01.003		CH power supply installed
2563.00.008		Keyboard wedge USB, for RS232 scale interface to PC USB interface (data cable 2550.03.002 required)
2550.03.020		USB Converter USB to RS232
2564.20.005		Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.002		PC software Scale Connecting, software for transferring scale data to PC-based software
2564.20.006		Software for linking scale to SAP R/3, to link scale via RS232, USB or Ethernet
2564.10.003		CD PC service software for print format design, dataset, printer installation
2562.01.004		Large display LED 95 mm, 5 pin plug with 15 m cable
2562.12.001		Second display LED 38 mm, 5 pin plug with 15 m cable
2562.70.002		Second display LCD 20 mm, 5 pin plug with 2 m cable
2551.50.001		Control light 30xx, power supply cable 2 m, interface cable 1.5 m (I/O module required)
2551.40.001		Control light 30xx, power supply cable 2 m, interface cable 1.5 m (I/O module required)
2563.40.011		I/O module, as installation kit for control light 2551.50.001
2563.40.012		I/O module, installed for control light 2551.50.001

Accessories

Order number Variation	Description
2507.01.002	Protective cover
2504.10.001	Floor stand with floor plate 200 x 200 mm, painted, approx. height: 1,150 mm
2504.11.001	Stand base, painted, 390x 390 mm
2504.20.001	Floor stand with floor plate 200 x 200 mm, stainless steel, approx. height: 1,150mm
2504.21.001	Stand base, stainless steel, 390 x 390 mm
2512.09.001	Name plate, blank
2512.09.002	Name plate, with entries
5751.01.001	Print format design, customer-specific
5751.01.002	Dataset format, customer-specific
5751.01.004	Dataset/print format installation of existing or provided data