

TPWI-PRO

TPWI "PRO" AISI 304 STAINLESS STEEL PALLET TRUCK SCALE



AISI 304 stainless steel pallet truck scale, suitable for use in moderately wet environments. Also available in a legal for trade approved version. Manufactured, calibrated and adjusted in Italy by Dini Argeo, using certified sample weights.

**The best solution
for advanced industrial
applications**

WEIGHING FEATURES

- Maximum lifting capacity: 2.000 kg; special capacities on request, up to 3.000 kg.
- Resolution:
 - > internal use: 0,2 / 0,5 kg
 - > approved: 0,5 / 1 kg
- Accuracy (weighing of goods on Europallet with distributed load):
 - > internal use: +/- 1 kg
 - > approved: according to CE certification (Directive 2014/31/EU)
- Calibration and Set-Up parameters configurable from keyboard or PC.

WHY CHOOSE TPWI-PRO

- AISI 304 thick stainless steel structure, manufactured entirely in Italy.
- Lifting pump manufactured in Italy, available on request for lifting up to 3.000 kg.
- Weight indicator with IP65 stainless steel waterproof case, easy to clean and resistant to harsh and corrosive environments.
- The large, high-contrast LCD display allows viewing even in low light conditions.
- Available in legal for trade approved version.
- The optional printer, with IP65 enclosure, can print out weighing data.
- Each pallet truck is tested and supplied with a calibration certificate to guarantee the stated accuracy.
- Special non-standard dimensions available on request.

TECHNICAL FEATURES

- Forks with low profile, only 85 mm.
- Forks dimensions: 1180 x 550 x 85 mm.
- Lifting range: from 85 to 205 mm.
- Pallet truck weight: 135 kg approx.
- Built with 4 Dini Argeo load cells, in IP68 stainless steel, for high weighing performance (IP69K on request).
- Bearing structure entirely made of extra thick AISI 304 stainless steel.
- Forks in AISI 304 stainless steel.
- Closed fork covers for increased protection of the double load wheels.
- Nylon guide wheels, polyurethane-coated for smooth running. 200 mm diameter ensures optimum smoothness and manoeuvrability
- Nylon loading rollers, polyurethane-coated.
- AISI 304 stainless steel lifting pump allowing controlled lowering of the forks.
- 25 mm LCD display.
- Membrane waterproof keyboard with 17 numeric/functional keys.
- Built-in rechargeable battery, with autonomy of approximately 50 hours.
- Battery charger 230Vac 50Hz with EU, UK, US, AU plug as standard (charging time aprox. 8 hours).
- Bi-directional RS232/C port configurable for printer connection.
- Bi-directional RS232/C port configurable for PC, radio modem or handheld terminal.
- Operating temperature: -10° / +40° C

THE EASIEST ONE TO RECALIBRATE AND REPAIR

- The only one without junction box: the adjustment of every single cell is conveniently carried out from the keyboard.
- Spare parts and wearing parts always available and ready for delivery.
- Specialized service centers throughout Italy.

MAIN FUNCTIONS

- The user can select the operating modes directly using the dedicated key*:
 - High resolution display x 10
 - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
 - Net/Gross
 - Lb to kg converter
 - Free conversion factor (for meter and litre counters etc.)
 - Weight totalizer
 - Formulizer
 - +/- controller with quick target and threshold input
 - Percentage weighing
 - Percentage batching with programmable target
 - Piece counter
 - Hold
 - Alibi memory (optional)
- Access to the user menu is gained using the dedicated key* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

** These quick access keys to the menus can be blocked by configuring a dedicated password.*

OTHER VERSIONS AVAILABLE

- Approved load capacity 600 / 1.500 kg, resolution 0,2 / 0,5 kg
- Approved load capacity 1.500 kg, resolution 0.5 kg
- Approved load capacity 1.500 / 2.500 kg, resolution 0,5 / 1 kg
- Load capacity 2.500 kg
- Other capacities / special resolutions: upon request.
- Other special versions: upon request.

TAILORED SIZES FOR EVERY NEED

- TPWI-PRO can be manufactured with special fork dimensions:
 - Lengths from 800 up to 2200 mm (up to 1800 mm in approved version)
 - Widths from 400 up to 900 mm (up to 680 mm in approved version)

DETAIL 1



VERSIONS

Available versions



Code	Max (kg)	d (kg)	M (kg)
TPWI-PRO	1000 / 2000	0,2 / 0,5	--
TPWIM-PRO M	1000 / 2000	--	0,5 / 1



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE